

DURACELL

PRODUCT DATA SHEET

DF4000R

Art.-Nr.: DB270

DURACELL®



DF4000R

PRODUCT DESCRIPTION

TECHNICAL DATA

Length [mm]	290
Head diameter [mm]	50
Tube diameter [mm]	37
Weight with batteries [g]	545
Weight without batteries [g]	407
Focusable	Yes
Main material	Aluminium alloy
Secondary material	ABS, PC
Battery cartridge	yes

ENERGY SUPPLY

Power source	Lithium Ionen Battery
Number of batteries	2
Battery type	18650
Exchangeable battery	Yes
Battery voltage [V]	7,4
Battery capacity [mAh]	2200
Battery energy ² [Wh]	19,24
Rechargeable	Yes
Charging time to 80% [min]	480
Charging plug	USB C 5V1A
Status display	yes
Other batteries can be used	no

CERTIFICATION

CE, UKCA, ANSI FL1

COUNTRY OF ORIGIN

China*

TECHNICAL SPECIFICATIONS

IP protection class	IP54
Break test (drop height) [m]	1,0
IK impact strength [J]	7
Operating temperature range [°C]	0 to +40

LIGHT FUNCTIONS

Low Power, Mid Power, Power

SOURCE OF LIGHT

Colour	White
Colour temperature [K]	6000 to 7000
Colour rendering index (CRI)	>70
LED Type	CREE-XFL05K

LIGHT VALUES¹

ANSI FL1	Boost	Power	Mid Power	Low Power
Luminous flux ¹ [lm]	0	4000	2000	500
Beamdistance ¹ [m]	0	200	150	60
Runtime ¹ [h]	0	2	3	6

SWITCH

Double front switch

FEATURES

Focusable, dimmable, rechargeable, O-LED display

TECHNOLOGIES*

Temperature Control System

